



型号/MODEL	U	T	W
Wave generator-A φ14	φ14H7	16.3 ^{±0.1}	5JS9/P9
Wave generator-A φ19	φ19H7	21.8 ^{±0.1}	6JS9/P9
Wave generator-A φ22	φ22H7	24.8 ^{±0.1}	6JS9/P9
		25.3 ^{±0.1}	8JS9/P9

型号/Model	输入2000r/min 转矩 Reduction ratio	启动转矩 Start torque 2000r/min input	启动峰值 Peak torque at start and stop	平均转矩 Average torque	允许最大转矩 Permissible maximum momentary torque	允许转速 (连续) Permissible rotational speed (Grease)	允许转速 (润滑油) Permissible rotational speed (Oil)	精度 Backlash	重量 Weight	设计寿命 Design life
50	76	7.8	216	22	108	11	382	39	4800	10000
80	118	12	304	31	167	17	568	58	3500	15000
100	137	14	333	34	216	22	647	66	515	15000
120	137	14	353	36	216	22	686	70	3.11	15000
160	137	14	372	38	216	22	686	70	15000	15000

设计	校对	审核	工艺

公众号

选型技术号

视图方式

重量

比例

共 1 张 第 1 张

A4

CHS MOTOR

广东川铭精工科技有限公司

组合型-直连杯型谐波减速机

CMS-32-(1)-U-1

请签字 (章) 回传
Please sign (seal) to return the call